



VICTOR REINZ™



Just Seal It! Liquid Sealants and Gasket Remover



1 FOR ALL

VictorReinz.com/JSI

Stay Safe. Go Beyond. With Dana Secure.

100% Protection From Counterfeit
Products. With Just 1 Scan.

1 SCAN
100% SECURE



Download App



Product Information | Installation Instructions |
Torque Specifications | Online Catalog | Datasheets
Video Tutorials | Newsletter Updates



VictorReinz.com/DanaSecure

REINZOSIL®

Fast-curing silicone sealant


For sealing flat surfaces with a gap of ≥ 0.15 mm (even without dismantling components).



Applications
















- Easy to position, shape and to apply
- Prevents corrosion of the sealing surfaces
- Non hazardous
- Acid-free curing means no damage to synthetic parts, electrical components, etc.
- Can be used on vertical and overhead surfaces



Just Seal It!

As an original equipment manufacturer and replacement part supplier, Dana delivers innovative sealing technologies of the highest quality under the brand name Victor Reinz®. All spare parts in the comprehensive product range meet the high standards of OEM quality.

Dana is a world leader in highly engineered solutions for improving the efficiency, performance, and sustainability of powered vehicles and machinery. Dana supports the passenger vehicle and commercial truck as well as industrial and stationary equipment applications.

Technical Data	REINZOSIL®			REINZOSIL®-t	REINZOPLAST	
	Tube 70 ml	Pressurized can 200 ml	Cartridge 310 ml	Tube 70 ml	Tube 80 ml	Cartridge 300 ml
Article no.	70-31414-10	70-31414-20	70-31414-40	70-31453-00	70-24571-20	70-24575-20
						
Sealing gap	≥ 0.15 mm / ≥ 0.006 in	≥ 0.15 mm / ≥ 0.006 in	≥ 0.15 mm / ≥ 0.006 in	≥ 0.15 mm / ≥ 0.006 in	≤ 0.15 mm / ≤ 0.006 in	≤ 0.15 mm / ≤ 0.006 in
Temperature						
Peak temperature (brief) [°C] / [°F]	320 / 608	320 / 608	320 / 608	200 / 392	300 / 572	300 / 572
Permanent temperature [°C] / [°F]	-50 to 250 / -58 to 482	-50 to 250 / -58 to 482	-50 to 250 / -58 to 482	-50 to 180 / -58 to 356	-50 to 250 / -58 to 482	-50 to 250 / -58 to 482
Durability of the medium incl. biofuel	++	++	++	++	++	++
Controllability	+	++	++	+	++	++
Skin building time	10-15 min.	10-15 min.	10-15 min.	10-15 min.	n.a.	n.a.
Curing properties						
Cures quickly, permanently elastic	++	++	++	++		
Does not cure, permanently plastic					++	++
Easy disassembling					++	++
Sealing without dismantling	++	++	++	++		
Packaging unit	 25x	 10x	 12x	 25x	 25x	 12x
Safety Warnings						

In-depth expertise for your day-to-day work:
our Technical Service Information.
Learn more now!

Technical Datasheet
Safety Datasheet
VictorReinz.com/JSI-Datasheet



VictorReinz.com/SocialMedia

Check out Victoria's practical tips:



 VictorReinz.com/Victoria

REINZOSIL[®]-t

The REINZOSIL transparent solution


Particularly suitable for sealing surfaces with visible joints and flat joints with a sealing gap of ≥ 0.15 mm (even without dismantling components).



- Easy to position, shape and to apply
- Can be used on vertical and overhead surfaces
- Prevents corrosion of the sealing surfaces
- Non hazardous
- Cures faster than other silicone sealants
- Low odour



Applications



Materials



REINZOPLAST

Unique permanently plastic wet sealing

Solvent-free, permanently plastic, non-curing polyurethane sealant with excellent flow properties for high-stress sealing joints with a gap of ≤ 0.15 mm, e.g., in applications subject to vibration.



- Easy to position, shape and to apply
- Prevents corrosion of the sealing surfaces
- Non hazardous
- Ready for immediate assembly
- Low odour





RE-MOVE

Fast gasket removal

Highly effective and long-lasting sealant remover.



- When sprayed, it gives an impermeable, high-adhesion, highly effective liquid film
- Can be used on vertical, sloped and overhead surfaces
- Also suitable for removing resin and paint residue
- Saves time and effort
- Easy handling

RE-MOVE	Article no.	Packaging unit	Safety Warnings
Spray can 300 ml	70-31415-00	12x 	



VictorReinz.com

Dana Incorporated
REINZ-Dichtungs-GmbH
Reinzstrasse 3-7
89233 Neu-Ulm
Germany

