



VICTOR REINZ™



Just seal it! Liquid Sealants and Gasket Remover
















1 FOR ALL



Just Seal It!

As an original equipment manufacturer and replacement part supplier, Dana delivers innovative sealing technologies of the highest quality under the brand name Victor Reinz®. All spare parts in the comprehensive product range meet the high standards of OEM quality.

Dana is a world leader in highly engineered solutions for improving the efficiency, performance, and sustainability of powered vehicles and machinery. Dana supports the passenger vehicle and commercial truck as well as industrial and stationary equipment applications.

Technical Data	REINZOSIL			REINZOSIL-t	REINZOPLAST	
	Tube 70 ml	Pressurized can 200 ml	Cartridge 310 ml	Tube 70 ml	Tube 80 ml	Cartridge 300 ml
Article no.	70-31414-10	70-31414-20	70-31414-40	70-31453-00	70-24571-20	70-24575-20
						
Sealing gap	≥ 0.15 mm / ≥ 0.006 in	≥ 0.15 mm / ≥ 0.006 in	≥ 0.15 mm / ≥ 0.006 in	≥ 0.15 mm / ≥ 0.006 in	≤ 0.15 mm / ≤ 0.006 in	≤ 0.15 mm / ≤ 0.006 in
Temperature						
Peak temperature (brief) [°C] / [°F]	320 / 608	320 / 608	320 / 608	200 / 392	300 / 572	300 / 572
Permanent temperature [°C] / [°F]	-50 to 250 / -58 to 482	-50 to 250 / -58 to 482	-50 to 250 / -58 to 482	-50 to 180 / -58 to 356	-50 to 250 / -58 to 482	-50 to 250 / -58 to 482
Durability of the medium incl. biofuel	++	++	++	++	++	++
Controllability	+	++	++	+	++	++
Skin building time	10-15 min.	10-15 min.	10-15 min.	10-15 min.	n.a.	n.a.
Curing properties						
Cures quickly, permanently elastic	++	++	++	++		
Does not cure, permanently plastic					++	++
Easy disassembling					++	++
Sealing without dismantling	++	++	++	++		
Packaging unit	 25x	 10x	 12x	 25x	 25x	 12x
Safety Warnings						

Based on decades of experience, Victor Reinz service parts are matched perfectly for efficient engine repair. Moreover, our technical service Information always keeps you up-to-date.



Technical Datasheet
VictorReinz.com/jsi-datasheet


Safety Datasheet
VictorReinz.com/jsi-datasheet

Watch Victoria's practical tips at:

 [VictorReinzSealingEN](https://www.youtube.com/VictorReinzSealingEN)

 [VictorReinz EMEA](https://www.facebook.com/VictorReinzEMEA)

 VictorReinz.com/victoria

 →  → 

 [linkedin.com/showcase/victor-reinz-emea](https://www.linkedin.com/showcase/victor-reinz-emea)
 VictorReinz.com/jsi

REINZOSIL®

Extremely high stability at high temperatures


Solvent-free, permanently elastic, fast-curing silicon sealant for sealing flat surfaces where there is a sealing gap $\geq 0.15 \text{ mm}$ / $\geq 0.006 \text{ in}$ (can also be applied to assembled components).



- Easy to position and shape and easy to apply
- Precise positioning, down to the last millimeter
- Protective cap prevents nozzle from blocking up
- Prevents corrosion of the sealing surfaces
- Non hazardous



- Acid-free curing means no damage to synthetic parts, electrical components, etc.
- Cures faster than other silicon sealants
- Low odour
- Can be used on vertical and overhead surfaces



REINZOPLAST®

Does not crack under pressure


Solvent-free, permanently plastic, non-curing, polyurethane sealant with high viscosity, for highly-stressed sealing joints without a sealing gap $\leq 0.15 \text{ mm}$ / $\leq 0.006 \text{ in}$, such as joints that are subject to vibrations.



- Easy to position and shape
- Prevents corrosion of the sealing surfaces
- For wet sealing without a sealing gap
- Non hazardous



- High viscosity
- Ready for immediate assembly
- Fully loadable within seconds
- Low odour





RE-MOVE

Fast gasket removal

Highly effective and long-lasting sealant remover.



- High-adhesion
- When sprayed, it gives an impermeable, high-adhesion, highly effective liquid film
- Can be used on vertical, sloped and overhead surfaces
- Also suitable for removing resin and paint residue

RE-MOVE	Article no.	Packaging unit	Safety Warnings
Spray can 300 ml	70-31415-00	12x 	




- Saves time and effort
- Easy handling
- Tackles the most difficult remnants
- For removing gaskets, gasket remnants and sealants



Stay Safe. Stay Informed. Dana Secure.

100% Protection from Counterfeit Products.
With Just 1 Scan!

1 SCAN
100% SECURE



INFO NEWS
TecDoc



Scan for App

Download App

Scan Label

Original!

Explore



VictorReinz.com/DanaSecure



Improved sustainability by eliminating the need to print product information on paper.

VictorReinz.com

Dana Incorporated
REINZ-Dichtungs-GmbH
Reinzstrasse 3-7
89233 Neu-Ulm
Germany

